



# GE® 7.4 cu. ft. Capacity Electric Dryer with Up To 120 ft. Venting and Sensor Dry

Model# GTD58EBPVDG



- **Sensor Dry** - This dryer with moisture sensor continually monitors temperature and moisture to determine the appropriate drying time to protect your laundry and prevent over-drying.
- **My Cycle Setting** - Make laundry simpler by saving your favorite dryer settings as a preset for future use with the My Cycle setting
- **Eco Dry** - Save energy and money on your utilities with the Eco Dry Dryer that reduces dry temperatures on select cycles without sacrificing performance
- **High Performance Venting** - Powerful airflow offers long-lasting performance from lint build-up and offers venting solutions up to 120 feet for greater installation flexibility
- **Wrinkle Care** - Minimize wrinkles with an extended tumble dryer that will continue to tumble with no heat to keep wrinkles from setting in after the dry cycle is complete.
- **Damp Alert** - Immediately know when clothes reach the ideal dampness level for ironing or air drying with this Damp Alert dryer.
- **Custom Dry Settings** - 10 custom dryer settings support a variety of specialty settings to protect clothing from unnecessary wear and tear.
- **Approx. Dimensions (in.)** - 46 H x 27 W x 30 1/2 D
- **Up Front Lint Filter** - Simplify the task of lint removal with our convenient upfront lint filter, enhancing airflow within the appliance and for your garments.

## FEATURES

Reverse-a-Door	Yes
Drum Type	Aluminized Alloy
Control Type	Electronic
Additional Dryer Features	Front Serviceable Glass Door LED Interior Light Lint Filter with Reminder Removable Up-Front Lint Filter
Dual Thermistors	Yes
Adaptive Capabilities	Cycle Time
Dryer Control Features	Damp Dry Signal Delay Dry - Up to 24 hours End-of-Cycle Signal LED Cycle Countdown LED Cycle Status Indicator Lights Wrinkle Care
Long Vent Capability	Up to 120 feet
Energy Saving Option	Yes - Eco Dry
Fuel Type	Electric
Additional Optional Cycles	Damp Alert Delay Dry My Cycle ecoDry
Moisture Sensor	Sensor Dry
Dryer Cycles	Active Wear Air Fluff Bulky / Bedding Cottons (Normal) Delicates Mixed Loads Quick Dry Sanitize Timed Dry Towels
Product Type	Top Load Matching
Temperature Options	High/Medium/Low/No Heat
Number of Cycles	12
Exhaust Options	4-Way (Rear; Right; Left & Bottom)
WiFi Connect	Optional (Requires part no. PBX23W00Y1)
Removable Up-Front Lint Filter	Yes
Style	Top-Loading
Heat Selections	4

- Reversible Dryer Door - Door can swing from either direction making it easier to access the last sock from the back of the drum
- Large Diffuser for Even Drying - A large internal heat diffuser allows for warm air to evenly spread throughout your clothes during the cycle, making this the ideal dryer for large loads and bulky items.
- Electricity-Powered Dryer - This dryer uses electricity, ensuring seamless integration with your current laundry setup.

*Have more questions? Please contact 1-800-626-2000*



**GE APPLIANCES**  
a Haier company

*CustomerNet*

# GE® 7.4 cu. ft. Capacity Electric Dryer with Up To 120 ft. Venting and Sensor Dry

Model# GTD58EBPVDG

---

## APPROXIMATE DIMENSIONS(HxDxW)

- 46 H x 27 W x 30.5 D

## CAPACITY

- Total Capacity (cubic feet) - 7.40cu ft

## APPEARANCE

- Door Style - Steel
- Control Knobs - Chrome
- Color Appearance - Diamond Gray

## WEIGHTS & DIMENSIONS

- Overall Height (in) - 46in
- Overall Width (in) - 27in
- Approximate Shipping Weight (lb) - 121lb
- Overall Depth (in) - 30 1/2in
- Height to Top of Case (in) - 38 1/2in
- Depth with Door Open 90° (in) - 51 3/4in
- Net Weight (lb) - 118lb

## POWER / RATINGS

- Volts/Watts/Amps - 240V,5600W,24A,60Hz or 208V, 4400W,22A,60Hz
- Watts - 5600/4400
- Electrical Requirements - 240V,5600W,24A,60Hz or 208V,4400W,22A,60Hz
- Hertz - 60

## WARRANTY

- Parts Warranty - Limited 1-year entire appliance
- Warranty Notes - See written warranty for full details
- Labor Warranty - Limited 1-year entire appliance

## CERTIFICATIONS

- Claims & Certifications - California Prop 65  
CEC Regulated

*Have more questions? Please contact 1-800-626-2000*