

PFD 404 U [208V]

Built-under fresh water dishwasher

w/ baskets for care homes, nursery schools and people w/ hygiene requirements.



- Max. cleaning performance*: 380 plates/h or 20 baskets/h
- First-class results thanks to fresh water system
- Extremely hygienic results – final rinse temperature of 185 (85) °F (°C)
- Safe and easy operation – automatic door opening
- Max. user convenience with M Touch Flex full-touch color display

* Depending on site conditions (temperature of incoming water / power connection) values given may vary.

EAN: 4002516577348 / Material number: 12066570 /
Old Material Number: 61040430NAM

| Construction type and design | |
|--|--------------------------|
| Model | Built-under dishwasher |
| Range | MasterLine |
| Model | Hygiene |
| Wash system | Fresh water front loader |
| Number of levels | 2 |
| Front | Stainless steel |
| Lid | Without lid |
| Side walls | Galvanised |
| Application | |
| Suitable for retirement and care homes | • |
| Suitable for hospitals | • |
| Suitable for child care facilities | • |
| Suitable for universities and schools | • |
| Performance data | |
| Tested virucidal efficacy | • |
| Certified hygiene | • |
| Shortest program duration in min. | 6 |
| Maximum final rinse temperature in °F (°C) | 185 (85) |
| Cleaning performance, plates/h | 380 |
| Cleaning performance, baskets/h | 20 |
| Possible to wash plastic baskets on two levels | • |
| Service life in wash cycles | 28000 |
| Control | |
| Control system | M Touch Flex |
| Max. delay start in h | 24 |
| Countdown indicator | • |
| Dishwashing programs [number] | 12 |
| Adjustable temperature holding time | • |
| Adjustable final rinse temperature | • |
| Program sequence indicator | • |
| Choice of display language | • |
| Language-neutral operation | • |
| Standard electrical connection | |
| Electrical connection | 2 AC 208V 60HZ |
| Heater rating in kW | 5.40 |
| Total connected load in kW | 5.80 |
| Fuse rating in A | 30 |
| Length of power cord in ft (m) | 6 (1.90) |
| NEMA plug: Twist Lock L6-30 | • |
| Possible voltage variant 1 | |
| Electrical connection | 3 AC 208V 60HZ |
| Heater rating in kW | 5.40 |
| Total connected load in kW | 5.80 |
| Fuse rating in A | 20 |
| Water connection/drainage | |
| Cold water [number] | 1 |
| Hot water [number] | 1 |

PFD 404 U [208V]

Built-under fresh water dishwasher

w/ baskets for care homes, nursery schools and people w/ hygiene requirements.



EAN: 4002516577348 / Material number: 12066570 /

Old Material Number: 61040430NAM

| | |
|--|--------------------|
| Required flow pressure in bar | 1.00-10.00 |
| Drain hose [DN] | 22 |
| Maximum delivery head for drain pump in inches (cm) | 39 3/8 (100) |
| Integrated water softener | • |
| Maximum water hardness in gpg (mmol/l) | 62.59 (10.70) |
| Water protection system | Waterproof system |
| Water consumption per wash cycle in gal (l) | 2.1 (8.00) gll (l) |
| Length of water inlet hose in inches (cm) | 67 (170) |
| Length of water drain hose in inches (cm) | 59 1/8 (150) |
| Dimensions and weight | |
| External dimensions, net height in inches | 32 5/16 (820) |
| Maximum height adjustment in inches (mm) | 60.00 |
| External dimensions, net width in inches | 23 9/16 (598) |
| External dimensions, net depth in inches | 23 7/16 (595) |
| External dimensions, gross height in inches | 36 1/4 (920) |
| External dimensions, gross width in inches | 26 7/16 (670) |
| External dimensions, gross depth in inches | 29 3/16 (740) |
| Usable space in wash cabinet, width in inches (mm) | 22 1/16 (559) |
| Usable space in wash cabinet, height in inches (mm) | 21 1/8 (536) |
| Usable space in wash cabinet, depth of upper basket in inches (mm) | 18 11/16 (474) |
| Usable space in wash cabinet, depth of lower basket in inches (mm) | 20 3/8 (516) |
| In-feed height above floor in inches (mm) | 8 9/16 (216) |
| Required niche width in mm | 23 5/8 (600) |
| Net weight [kg] | 166 (75) |
| Gross weight in lbs. | 188 (85) |
| Maximum floor load in N/m ² | 1200 |
| Emission values | |
| Emission sound pressure level in workplace (LpA) | 45 dB(A) re 20 µPa |
| Sound power (LwA) in dB(A) re 1 pW | 57.0 |
| Heat dissipation into the room in MJ/h | 1.44 |
| Programs | |
| Normal Plus | • |
| Rapid | • |
| Normal | • |
| SaniWash | • |
| SaniWash Plus | • |
| Cold/Pre-wash | • |
| Glasses | • |
| Beer glasses | • |
| Cutlery | • |
| Plastic | • |
| Intensive | • |
| Reactivation | • |
| Drainage by pump | • |
| Baskets | |
| Height-adjustable upper basket | • |
| Combinable with APFD 210 bottle basket | • |

PFD 404 U [208V]

Built-under fresh water dishwasher

w/ baskets for care homes, nursery schools and people w/ hygiene requirements.



EAN: 4002516577348 / Material number: 12066570 /
Old Material Number: 61040430NAM

Features

| | |
|---|--------------------------|
| Drying | AutoOpen assisted drying |
| AutoClose | • |
| 1 Combi dispenser/door for powder and liquid media | • |
| In-door salt container | • |
| Door lock, protected by code | • |
| Safe mode | • |
| Perfect GlassCare | • |
| Highly effective filter system with filter monitoring | • |
| Aerosol steam condenser | • |
| Wash cabinet made from high-quality stainless steel | • |
| Optical interface | • |
| A wide range of accessories (optional) | • |

Connection options

| | |
|---|---|
| External dispenser module for liquid cleaning agent | • |
| Wi-Fi | • |

Standards, test certificates, and symbols

| | |
|--|---|
| Complies with Machinery Directive 2006/42/EC | • |
| Splash protection IPX1 | • |
| EMC radio suppressed | • |
| DIN 10512 | • |
| DIN EN 17735 | • |
| ETL | • |
| ADA compliant | • |