



Lone Star Spirit **XL**

SPC COLLECTION



LI-TS207 Sea Shell

Lone Star Spirit XL boasts versatile and refined exotic wood-like designs with the latest Embossed in Register (EIR) technology and planks measuring 6 feet long and 9 inches wide. The collection is also water-resistant, scratch-resistant, anti-bacterial cured, easy-to-install, low maintenance, eco-friendly, durable and long-lasting, making it perfect for both budget conscious DIY-ers and luxury-minded homeowners.



Waterproof



Indent Resistant



Sound Tested



Pet Friendly



Formaldehyde Free



Phthalate Free

SPECIFICATIONS

Material Type	SPC	Pad Type	Antibacterial + Acoustic	Per Box	5 pieces	22.65 sq.ft.	50 lbs.
Plank Size	6' x 9"	Edge Profile	Painted Bevel	Pallet	40 boxes	906.1 sq.ft.	2,050 lbs.
Total Thickness	6.5 mm	Installation Type	Floating	Container	960 boxes	21,746 sq.ft.	
Core Thickness	5 mm	Click System	Uniclic				
Wear Layer	20 mil	Plank Repeat	10				
Attached Pad	Yes	Texture/Style	Embossed in Register				
Pad Thickness	1.5 mm	Finish	UV Acrylic				



CERTIFIED BY SCS Global Services

COLORS



LI-TS201 Artisan Touch



LI-TS202 Backyard Garnish



LI-TS203 Oak Exotica



LI-TS204 Oak Dry-Aged



LI-TS205 Forgotten Bark



LI-TS206 Shangri La



LI-TS207 Sea Shell



LI-TS208 Ballroom Rodeo

MOULDINGS



End Cap



Flush Stair Nose



Quarter Round



Reducer



Stair Tread



T-Moulding

TESTING

ASTM E648	Fire Rating	Class 1
ASTM D2047	Coefficient of Friction	Standard Neolite 0.93
ASTM F970	Static Load Limit	0.004 in.
E492	IIC - Impact Sound Rating	61 db
E90	STC - Sound Transmission Loss	53 db
ASTM F387	Overall Thickness	0.265 in.

ASTM F410	Average Wear Layer Thickness	20.7 mil
ASTM F2199	Dimensional Stability, Curl After Heat	Passes
ASTM F1914	ASTM F2199	Passes
ASTM F1514	Resistance to Heat	Passes
ASTM F1514	Resistance to Light	Passes

Phthalate Free

Floor Score Certified