

COORDINATING MOLDINGS for

WE CREATE **COORDINATING MOLDINGS**, NOT PERFECT MATCHES, BECAUSE YOUR FLOORS AND OUR MOLDINGS USE DIFFERENT PRINTING METHODS & MATERIALS.

Available Products

The overall flooring assembly thickness refers to the total thickness of all members of the floor installation being laid upon the subfloor. This typically is comprised of the flooring plank, e.g. the underlayment, either attached or loose lay and any additional vapor barriers.

Slim Trim-P29

For Flooring Up to 1/4" (6.35 mm)
3-in-1: Reducer, T-Molding, & End Cap



Includes Track
& 1 Shim

Slim Trim-P32

For Flooring Up to 3/4" (19 mm)
3-in-1: Reducer, T-Molding, & End Cap



Includes Tree
of 8 Dowels

VersaEdge Extra Tall

Stair Nose
1.5" Height



VT-VEX-Shims are
available for flush
install. Please inquire.

Slim Cap-P29

End Cap



Includes Track
& 1 Shim

Quarter Round

Standard or Moisture Proof



Reducer

Moisture Proof



Versatrack

For Flooring 9/32-15/32" (7-12 mm)
Optional Use with Reducer, T-Molding, & End Cap



Slim Trim-P54

For Flooring 1/4-3/8" (6.35-9.5 mm)
3-in-1: Reducer, T-Molding, & End Cap



Includes Track
& 2 Shims

Slim Trim-P31

For Flooring Up to 3/4" (19 mm)
3-in-1: Reducer, T-Molding, & End Cap



Includes Track & Shim
and Tree of 8 Dowels

VersaEdge - Standard

Stair Nose
1" Height



VT-VE-Shims are
available for flush
install. Please inquire.

Slim Cap-P54

End Cap



Includes Track
& 2 Shims

End Cap

Moisture Proof



T-Molding

Moisture Proof



Versatrack Shim

For Flooring 15/32-5/8" (12-16 mm)
Optional Use with Reducer, T-Molding, & End Cap



Used with
Versatrack

All Moldings are 94" Long
1 Piece minimum

Terms: Credit applications are under the "How To Order" tab on the Versatrim Website.

This is a custom product and is non-returnable

adore[®]
luxury flooring

Technical Information

Sizes & Material

Slim Trim

Moisture Proof

Functions as a Reducer, T-Molding, and End Cap.

Surface Material: High Wear Resistant Aluminum Oxide Laminate

Core Material: Slim Trim: PVC

SlimTrack

Included with Slim Trim-P29, P31, P54 and

Slim Cap-P29 and P54

Material: Cold Roll Steel.

Versatrack Shim

1 Included with Slim Trim-P29, P31 & Slim Cap-P29
and 2 with Slim Trim-P54 and Slim Cap-P54

Material: Standard HDF

Dowel

Included with Slim Trim-P32

Material: Polystyrene

VersaEdge Extra Tall

Moisture Proof

Stair Nose - 1.5" Height

Surface Material: High Wear Resistant Aluminum Oxide Laminate

Core Material: Aluminum

VersaEdge Standard

Moisture Proof

Stair Nose - 1" Height

Surface Material: High Wear Resistant Aluminum Oxide Laminate

Core Material: PVC

VT-VE(X) Shims (Sold Separately)

Material: Standard MDF/HDF

Slim Cap

Moisture Proof

Surface Material: High Wear Resistant Aluminum Oxide Laminate

Core Material: PVC

Quarter Round

Standard or Moisture Proof

Surface Material: Decorative Paper

Core Material: Standard: Standard MDF

Moisture Proof: Exterior Grade Composite Wood Product

End Cap

Moisture Proof

Surface Material: High Wear Resistant Aluminum Oxide Laminate

Core Material: Exterior Grade Composite Wood Product

Reducer

Moisture Proof

Surface Material: High Wear Resistant Aluminum Oxide Laminate

Core Material: Exterior Grade Composite Wood Product

T-Molding

Moisture Proof

Surface Material: High Wear Resistant Aluminum Oxide Laminate

Core Material: Exterior Grade Composite Wood Product

Versatrack (Sold Separately)




















To be used with End Cap, Reducer, and T-Molding for flooring 9/32-15/32" (7-12 mm).

Material: Cold Roll Steel

Versatrack Shim (Sold Separately)

To be used with End Cap, Reducer, and T-Molding in conjunction with the Versatrack for flooring from 15/32-5/8" (12-16 mm).

Material: Standard HDF



FOR INSTALLATION INFORMATION, TIPS, AND ADVICE GO TO: INSTALLATIONADVICE.COM