



TimbrCORE™

LP-82 Collection

Plank Size:	8.03" x 47.64" (204mm x 1210mm)
Thickness:	8mm + 2mm pad
Core:	ULTRACORE™
Finish:	High Performance, Scratch Resistant (HPSR)
Wear Rating:	AC4
Waterproof:	Yes
Bevel:	4-Sided Micro
Gloss:	Low
Texture:	Timbr
Installation:	Angle/Tap on All Grades and Levels
Res. Warranty:	Limited Lifetime Residential
Com. Warranty:	5-Year Lt. Commercial



GENERAL DATA

DESCRIPTION	METHOD	RESULT	DETAILS
Class of Use	EN13329-32	Class 32	All Residential plus general commercial
Abrasion Resistance	NALFA LF-01	AC4	IP ≥ 4000 cycles
Impact Resistance	NALFA LF-01	Big Ball: ≥ 1000mm, Small Ball: ≥ 200mm	
Stain Resistance	NALFA LF-01	< 20	No more than slight effect
Sound Transmission	ASTM E90, E413	STC60	152mm slab, drop ceiling
Impact Insulation Class IIC	ASTM E429, E989	IIC63	152mm slab, drop ceiling
Thickness Swell Test	NALFA-01	PASSED	≤ 16% (±1%)
NALFA Surface Swell Test	NALFA LF-01	< 0.5mm	Passed

ENVIRONMENTAL CERTIFICATES

Green Guard	GOLD
CARB 2	Compliant
TSCA Title VI	Compliant
Content	No heavy metals + lead/cadmium present
Dangerous Substances	No carcinogenic, mutagenic or reprotoxic substances present (class 1A & 1B)
Plasticizer	ORTHOPHTHALATES FREE

