

LEGENDARY SDA® TECHNOLOGY

PINNACLE RING RADIATOR TWEETER

Developed by Polk Audio, the new high definition Pinnacle Ring Radiator™ Tweeter delivers ultra-clear, crisp highs, without unwanted distortions.

PATENTED SDA-PRO™ TECHNOLOGY

Polk-patented SDA (Stereo Dimensional Array) technology creates an expansive soundstage and detailed stereo image, while delivering a multi-dimensional sound experience.

NEW TURBINE CONE

The Turbine Cone™ combines a Polk-proprietary foam core and molded turbine geometry to dramatically increase stiffness and damping, without adding mass. This results in a smooth, detailed mid-range and effortless bass. Hear every detail.

CABINETS BUILT FOR BETTER PERFORMANCE

Polk Legend cabinets, braces and internal enclosures are carefully engineered to minimize unwanted internal standing waves and eliminate unwanted resonances.

BETTER BASS BY DESIGN WITH ENHANCED POWER PORT®

Hear and feel the difference; Polk Enhanced Power Port produces less port noise and more bass than traditionally ported loudspeakers.

DESIGNED FOR 3D AUDIO

The L900 height module is Dolby Atmos® certified and designed to meet DTS:X® specifications. (Sold separately)



POLK LEGEND SERIES



MODELS	L100 Standmount (Pair)	L200 Standmount (Pair)	L400 Center Channel	L600 Floorstanding Loudspeaker	L800 SDA-PRO Floorstanding Loudspeaker	L900 Height Module (Pair)
TRANSDUCER						
Tweeter	1" Ring Radiator	1" Ring Radiator	1" Ring Radiator	1" Ring Radiator	1" Ring Radiator (x2)	0.75" Ring Radiator
Mid-range/Mid-bass	5.25"	6.5"	4"	5.25"	5.25" (x2)	4"
Woofers	-	-	6.5" (x2)	7" (x2)	10" (x2)	-
Frequency Response (-3dB limits)	57Hz-38kHz	46Hz-38kHz	55Hz-38kHz	34Hz-38kHz	32Hz-38kHz	150Hz-30kHz
Overall Frequency Response	43Hz-50kHz	38Hz-50kHz	42Hz-50kHz	28Hz-50kHz	24Hz-50kHz	90Hz-40kHz
Steady State Recommended	30-160W	30-200W	25-300W	30-300W	25-300W	30-100W
Recommended Amplifier Power	70W	80W	80W	100W	100W	-
2.83V Sensitivity	85.5dBSPL@2.83V	85.5dBSPL@2.83V	87.5dBSPL@2.83V	86dBSPL@2.83V	87dBSPL@2.83V	86dBSPL@2.83V
Impedance	4Ω (3.0Ω min.)	4Ω (3.0Ω min.)	4Ω (3.4Ω min.)	4Ω (3.3Ω min.)	4Ω (2.8Ω min.)	4Ω (2.8Ω min.)
CROSSOVER						
Tweeter/Mid-range Crossover Frequency	2.9kHz	2.6kHz	2.7kHz	2.9kHz	2.8kHz	2kHz
Mid-range/Mid-bass Crossover Frequency	-	-	260Hz	410Hz	370Hz	-
MEASUREMENTS						
Dimensions W x H x D (in / mm)	7.78 x 13.64 x 11.29 in 197.5 x 346.4 x 286.8 mm	8.33 x 15.66 x 13.30 in 211.5 x 397.9 x 337.8 mm	26 x 9.47 x 13.44 in 660.4 x 239.1 x 341.5 mm	12.96 x 46.69 x 15.9 in 329.3 x 1185.9 x 404 mm	17.94 x 48.60 x 17.38 in 455.6 x 1234.5 x 441.4 mm	7.01 x 9.84 x 3.3 in 178 x 250 x 83.9 mm
Product Weight (each) (lbs / kg)	16.9 lbs / 7.65 kg	22 lbs / 10 kg	40.8 lbs / 18.5 kg	77.8 lbs / 35.3 kg	118 lbs / 53.5 kg	3.3 lbs / 1.5 kg
Shipping Weight (lbs / kg)	37.6 lbs / 17.05 kg	49.8 lbs / 22.6 kg	46.2 lbs / 20.95 kg	90.5 lbs / 41.05 kg	151 lbs / 68.5 kg	8.4 lbs / 3.8 kg
CABINETRY						
Mid-range Enclosure Type	-	-	Sealed	Sealed	Sealed	-
Woofer Enclosure Type	Power Port	Power Port	Power Port	Power Port	Power Port	-
Available Finishes	Brown Walnut / Black Ash	Brown Walnut / Black Ash	Brown Walnut / Black Ash	Brown Walnut / Black Ash	Brown Walnut / Black Ash	Black
Feet	-	-	-	Spike and Pad	Spike and Pad	-



THE LEGEND STORY

PERFECTING THE STEREO LOUDSPEAKER

For more than 45 years, Polk Audio has been designing and voicing amazing sounding loudspeakers, sound bars and smart speakers. Polk develops, prototypes, tests and listens to every aspect of its loudspeakers in their Baltimore, Maryland USA engineering facility.

From innovation in tweeter design to the new SDA-PRO™ (Stereo Dimensional Array), Polk Legend delivers great sound that's accessible to all.



polk

EXPECT GREAT SOUND™

©2019 POLK AUDIO. ALL RIGHTS RESERVED.

Polk is a registered trademark of Polk Audio, LLC. All other trademarks are the property of their respective owners.

polk
LEGEND™



L100 | L200 | L400 | L600 | L800 | L900