

Revel F228Be



PERFORMA **Be**⁴™



Features

- 1" Beryllium Dome Tweeter
- 5th-generation Acoustic Lens Waveguide
- Deep Ceramic Composite (DCC) Cone Midrange and Woofer
- High-order Crossovers with Film Capacitors and Air Core Inductors
- Magnetically Attached Grilles
- Four Premium High-gloss Finishes Available; Black, White, Walnut and Metallic Silver

Specifications

Description	3-way Floorstanding Loudspeaker
Low Frequency Driver Size and Material	Dual 8" (200mm) Deep Ceramic Composite (DCC) Aluminum Cones with Cast Frames
Mid Frequency Driver Size and Material	5.25" (130mm) DCC Aluminum Cone with Cast Frame
High Frequency Driver Size and Material	1" (25mm) Beryllium Dome with Acoustic Lens Waveguide
Recommended Amplifier Power	50 – 350 Watts
Nominal Impedance	8 Ohms
Loudspeaker Sensitivity (2.83 V/1m)	90dB
Frequency Response	27Hz – 44kHz (-6dB)
Crossover Frequency	260Hz; 2.1kHz
Dimensions (H x W x D)	46.5 x 11.8 x 13.2" (1181 x 302 x 335mm)
Weight	82 lbs (37.2kg)
Inputs	Dual Gold-plated Binding Posts with Shorting Straps

Revel F228Be

