



# WOODWORK

## 5M502

Style Name  
Style Number  
Construction  
Class / ASTM F1700  
Attached Underlayment  
Finish

**WOODWORK**  
**5M502**  
**Heavy Commercial Luxury Vinyl**  
**Class III Printed Film Vinyl Tile, Type B (embossed)**  
**No**  
**ExoGuard®**


Nominal Dimensions  
Actual Dimensions  
Wear Layer Thickness  
Overall Thickness  
Installation  
Recommended / Required Adhesive

U.S.	Metric
<b>9 in w, 60 in l</b>	<b>23 cm w, 152.5 cm l</b>
<b>9 in w, 60 in l</b>	<b>22.86 cm w, 152.4 cm l</b>
<b>20 mil (0.02 in)</b>	<b>0.51 mm</b>
<b>0.197 in</b>	<b>5 mm</b>
<b>Direct Glue, Perimeter Glue or Loose Lay</b>	
<b>Shaw 4100 or S150</b>	

### Packaging

Pieces per box	<b>6 pcs</b>	
Area per box	<b>22.5 sq ft</b>	<b>2.09 sq m</b>
Weight per box	<b>41.67 lbs</b>	<b>18.9 kg</b>

### Recommended Installation Method



### Performance Testing

Static Load (ASTM F970)	<b>Passes (Modified), 1000 PSI</b>
Resistance to Heat (ASTM F1514)	<b>Passes</b>
Resistance to Light (ASTM F1515)	<b>Passes</b>
Radiant Panel (ASTM E648)	<b>Passes, Class I</b>
Slip Resistance (ASTM D2047)	<b>ADA compliant</b>

Test Reports may be included or listed by the manufacturing/inventory style number as opposed to the noted selling style number.

### Warranties

**Commercial Limited Underbed Bond Warranty S150/4151/LokWorx+ Resilient**  
**Resilient 15 Year Commercial Limited Warranty**

### Environmental

Indoor Air Quality	<b>FloorScore® Certified</b>
Recycled Content	<b>Pre-consumer - 0%, Post-consumer - 0%</b>

Specifications are subject to nominal manufacturing variance.  
Material supply and/or manufacturing processes may necessitate changes without notice.

